

Serija COMPACT, plastično ventilaciono kolo HCF(B/T)



HCFB/HCFCT



Konstruktivna konfiguracija modela Ø800 - Ø1000

Niskoprotfilni zidni aksijalni ventilator sa plastičnom elisom od fiberglasa. Postoje monofazni HCFB i trofazni modeli HCFT zaštite IP65 (osim za modele 800, 900 i 1000 koji imaju IP55 zaštitu) i izolacije F (radna temperatura od -40°C do 70°C, osim kod modela 800 i 1000 za koje je od -20°C do 40°C) i sa termičkom zaštitom (osim kod modela 800 i 1000).

Motor

Dostupni su modeli sa 2, 4 ili 6 polova, u zavisnosti od modela. Moguća je i naponska regulacija preko autotransformatora, osim za modele sa 2 pola i /4-630, /4-710, T/800, T/900 i T/1000. Kod modela od 800 do 1000 regulacija se vrši frekventnim regulatorom.

Napajanje:

Monofazno 230V-50Hz
Trofazno 230/400V-50Hz ili 400V-50Hz

Dodatne informacije:

Kretanje vazduha motor-ventilaciono kolo (smer A).

Na zahtev:

Ventilaciono kolo-Motor (smer B), po zahtevu. Zaštitna mreža za modele 800-1000.



PRIMENA



Magacini



Radionice



Komerijalni prostori



Parkinzi



Staklenici



Poljoprivreda



Farbare



Klimatizacija



Generatori



Prehrambena industrija



Sušare

Kod	Model	Broj (o/min)	Ø Prečnik (mm)	Snaga motora (W)	Maks. jačina struje (A)		Nivo šuma (dB(A))	Maks. protok (m³/h)	Težina (kg)	Regulacija brzine*	Cena 1G
					230V	400V					
TROFAZNI											
5603962100	HCFT/2-250/H	2.500	250	250	0,9	0,5	65	2.160	5	-	255,00
5603959700	HCFT/4-250/H	1.330	250	60	0,3	0,2	52	1.220	5	RMT-1,5	235,00
5602513300	HCGT/2-315/G	2.650	315	410	1,4	0,8	70	3.400	7	-	370,00
5602186800	HCFT/4-315/H	1.300	315	150	0,6	0,3	54	2.350	7	RMT-1,5	241,00
5605757800	HCFT/6-315/H	875	315	80	0,4	0,2	45	1.560	7	RMT-1,5	300,00
5602514100	HCGT/2-355/I	2.380	355	520	1,6	0,9	71	4.400	8	-	575,00
5602187600	HCFT/4-355/H	1.260	355	200	0,8	0,5	58	3.490	8	RMT-1,5	296,00
5602946500	HCFT/6-355/H	875	355	90	0,5	0,3	50	2.210	8	RMT-1,5	325,00
5602049800	HCFT/4-400/H	1.350	400	300	1,4	0,8	60	5.070	9	RMT-1,5	310,00
5602718800	HCFT/6-400/H	830	400	110	0,5	0,3	52	3.400	9	RMT-1,5	338,00
5602188400	HCFT/4-450/H	1.230	450	500	1,7	1,0	65	6.760	13	RMT-1,5	409,00
5602458100	HCFT/6-450/H	835	450	190	0,8	0,5	53	4.550	13	RMT-1,5	413,00
5603159400	HCFT/8-450/H	660	450	130	0,7	0,4	51	3.500	13	RMT-1,5	419,00
5602189200	HCFT/4-500/H	1.350	500	660	2,7	1,6	68	9.200	16	RMT-2,5	449,00
5602682600	HCFT/6-500/H	840	500	250	0,9	0,5	56	5.820	16	RMT-1,5	430,00
5602360900	HCFT/8-500/H	625	500	150	0,7	0,4	49	4.660	16	RMT-1,5	504,00
5602003500	HCFT/4-560/H	1.320	560	1.210	3,9	2,3	71	12.480	22	RMT-2,5	637,00
5602693300	HCFT/6-560/H	900	560	410	1,6	0,9	59	8.260	22	RMT-1,5	517,00
5603305300	HCFT/8-560/H	610	560	230	1,0	0,6	55	5.990	22	RMT-1,5	533,00
5602091000	HCFT/4-630/H	1.420	630	1.550	5,2	3,0	72	17.060	25	-	703,00
5602085200	HCFT/6-630/H	810	630	460	2,0	1,2	60	11.000	25	RMT-1,5	513,00
5602674300	HCFT/8-630/H	635	630	310	1,3	0,8	57	8.340	25	RMT-1,5	520,00
5604973700	HCFT/4-710/H	1.350	710	2.200	7,0	4,0	75	22.150	27	-	880,00
5604974500	HCFT/6-710/H	920	710	1.100	4,9	3,3	66	16.500	27	-	655,00
5604975200	HCFT/8-710/H	670	710	450	2,0	1,2	60	11.960	27	-	733,00
5604262500	HCFT/4-800/L-X (1,5kW)	1.420	800	2.300	6,6	3,8	79	24.960	37	VFKB-48	949,00
5604263300	HCFT/4-800/H-X (3kW)	1.430	800	4.200	12,6	7,3	82	32.600	52	VFKB-48	1.123,00
5604264100	HCFT/6-800/L-X (0,55kW)	900	800	1.180	3,9	2,2	70	19.370	31	VFKB 45	814,00
5604265800	HCFT/6-800/H-X (0,75kW)	940	800	1.220	4,3	2,5	72	22.000	36	VFKB 45	928,00
5604266600	HCFT/8-800/L-X (0,25kW)	710	800	580	2,2	1,3	63	14.000	63	VFKB 45	834,00
5604267400	HCFT/8-800/H-X (0,37kW)	690	800	700	3,0	1,7	65	17.160	64	VFKB 45	977,00
5605717700	HCFT/4-900/L-X (3kW)	1.400	900	4.400	11,3	6,5	83	35.000	94	VFTM-TRI	1.285,00
5605718500	HCFT/4-900/H-X (5,5kW)	1.400	900	7.200	-	12,0	87	45.000	110	TM-TRI	1.914,00
5605719300	HCFT/6-900/L-X (1,1kW)	950	900	1.400	5,7	3,3	74	23.500	86	FKB 45	1.018,00
5605720100	HCFT/6-900/H-X (1,5kW)	950	900	2.330	6,9	4,0	78	30.000	93	VFKB 45	1.062,00
5605721900	HCFT/8-900/L-X (0,37kW)	700	900	720	2,7	1,6	69	17.500	83	VFKB 45	985,00
5605722700	HCFT/8-900/H-X (0,75kW)	700	900	1.100	4,5	2,6	72	22.500	90	VFKB 45	1.126,00
5604268200	HCFT/4-1000/L-X (4kW)	1.400	1.000	4.400	12,3	7,1	84	42.000	67	VFKB-48	1.236,00
5111936000	HCFT/4-1000/H-X (5,5kW)	1.460	1.000	7.200	-	12,0	87	54.000	95	VFTM-TRI	2.678,00
5604269000	HCFT/6-1000/L-X (1,1kW)	940	1.000	1.400	5,6	3,2	75	28.000	54	FKB 45	1.132,00
5604271600	HCFT/6-1000/H-X (1,5kW)	950	1.000	2.330	7,6	4,4	78	36.400	62	VFKB 45	1.215,00
5604270800	HCFT/8-1000/L-X (0,37kW)	700	1.000	720	3,0	1,7	68	20.490	68	VFKB 45	1.236,00
5604272400	HCFT/8-1000/H-X (0,75kW)	725	1.000	1.100	4,6	2,7	72	27.040	71	VFKB 45	1.412,00

Kod	Model	Brzina (o/min)	Ø Prečnik (mm)	Snaga motora (W)	Maks. jačina struje (A)		Nivo šuma (dB(A))	Maks. protok (m³/h)	Težina (kg)	Regulacija brzine*	Cena 1G
					230 V	400 V					
MONOFAZNI											
5603896100	HCFB/2-250/H	2.500	250	250	1,2	–	65	2.160	5	–	267,00
5603891200	HCFB/4-250/H	1.330	250	60	0,3	–	52	1.215	5	REB-1	247,00
5602511700	HCGB/2-315/L	2.500	315	380	1,7	–	70	3.260	7	–	370,00
5602069600	HCFB/4-315/H	1.300	315	100	0,6	–	54	2.350	7	REB-1	256,00
5605756500	HCFB/6-315/H	825	315	80	0,4	–	45	1.560	7	REB-1	324,00
5602512500	HCGB/2-355/J	2.000	355	460	2,2	–	71	4.000	8	–	618,00
5602184300	HCFB/4-355/H	1.225	355	200	1,0	–	58	3.490	8	REB-2,5	312,00
5602119900	HCFB/6-355/H	800	355	90	0,5	–	50	2.210	8	REB-1	345,00
5602075300	HCFB/4-400/H	1.200	400	340	1,6	–	60	5.070	9	REB-2,5	333,00
5602081100	HCFB/6-400/H	750	400	110	0,6	–	52	3.400	9	REB-1	360,00
5602070400	HCFB/4-450/H	1.290	450	480	2,3	–	65	6.760	13	REB-2,5	431,00
5602095100	HCFB/6-450/H	835	450	220	1,2	–	53	4.550	13	REB-2,5	433,00
5602148800	HCFB/8-450/H	625	450	130	0,7	–	48	3.500	13	REB-1	440,00
5602185000	HCFB/4-500/H	1.290	500	650	3,0	–	68	9.200	16	REB-5	472,00
5602145400	HCFB/6-500/H	840	500	290	1,6	–	56	5.820	16	REB-2,5	455,00
5603234500	HCFB/8-500/H	605	500	160	0,9	–	49	4.660	16	REB-1	460,00
5602002700	HCFB/4-560/H	1.250	560	980	4,9	–	71	12.480	22	REB-5	649,00
5602071200	HCFB/6-560/H	900	560	420	2,4	–	59	7.870	22	REB-2,5	507,00
5603241000	HCFB/8-560/H	610	560	240	1,3	–	51	5.990	22	REB-2,5	515,00
5602082900	HCFB/4-630/H	1.200	630	1.700	7,6	–	72	17.060	25	–	735,00
5602072000	HCFB/6-630/H	800	630	510	2,6	–	60	10.750	25	REB-5	535,00
5603125500	HCFB/8-630/H	585	630	320	1,7	–	52	8.340	25	REB-2,5	543,00
5604976000	HCFB/6-710/H	900	710	1.300	5,7	–	66	17.570	27	–	802,00
5604977800	HCFB/8-710/H	625	710	480	2,4	–	60	11.960	27	–	712,00

* Regulacija kod trofaznih modela (RMT) ili korišćenje frekventnog konvertora (VFKB / VFTM) se preporučuje na 400V.

Pribor za montažu (Pogledati cene na stranama gde su delovi za montažu)

Model HCFB/HCFB HCB(B/T)	Zaštitna mreža		Nadpritisna žaluzina	
	na usisu	na potisu	plastična	aluminijumska
250	DEF-250 D	–	PER-250 W	PER-250 CN
315	DEF-325 D	–	PER-355 W	PER-355 CN
355	DEF-375 D	–	PER-355 W	PER-355 CN
400	DEF-450 D	–	PER-400 W	PER-400 CN
450	DEF-450 D	–	PER-450 W	PER-450 CN
500	DEF-525 D	–	PER-500 W	PER-500 CN
560	DEF-630 D	–	PER-560 W	PER-630 CN
630	DEF-630 D	–	PER-630 W	PER-630 CN
710	DEF-800 D	–	PER-710 W	PER-710 CN
800	DEF-800 D	DEF- 800 AN	PER-800 W	PER-800 CN
900	DEF-1000 D	DEF- 900 AN	PER-1000 W	PER-1000 CN
1000	DEF-1000 D	DEF-1000 AN	PER-1000 W	PER-1000 CN
HCFT / 4-1000 / H	DEF-1000 D	DEF-1001 AN	PER-1000 W	PER-1000 CN