

Aksijalni dvobrzinski ventilatori

Two Speed Axial Fans

Model	Brzina / Speed	o/min / rpm	A	W	m ³ /h	Kondenzator / Capacitor μ f	Cena/Price
JAV4MDI-5-200	HS	1350	0,14	30	425	1	51,00
	LS	950	0,05	10	300		
JAV4MDI-5-250	HS	1380	0,20	44	860	1,5	62,00
	LS	1200	0,12	26	750		
JAV4MDI-5-300	HS	1350	0,40	90	1750	3	64,00
	LS	1050	0,25	55	1350		
JAV4MDI-5-350	HS	1350	0,60	130	2670	4	79,00
	LS	1160	0,47	110	2300		
JAV4MDI-5-400	HS	1350	0,85	185	3500	6	95,00
	LS	1150	0,65	145	2800		
JAV4MDI-5-450	HS	1330	1,10	240	4800	8	109,00
	LS	1100	0,80	180	3950		
JAV4MDI-5-500	HS	1350	2,00	420	6500	10	-
	LS	1150	1,70	360	4800		
JAV4MDI-5-550	HS	1350	2,50	540	7500	12	183,00
	LS	1100	2,30	490	5600		
JAV4MDI-5-630	HS	1400	3,70	800	10800	16	230,00
	LS	1300	3,20	680	8300		
JAV6TDI-7-710	HS	900	2,00	1100	15500	-	408,00
	LS	600	1,40	750	11600		
JAV6TDI-7-800	HS	900	3,70	1850	25000	-	na upit / by request
	LS	700	2,30	1250	19000		
JAV6TDI-7-900	HS	910	4,00	2000	27000	-	na upit / by request
	LS	750	2,40	1300	21500		

ATEST



- a) Pogodni su za komercijalnu i industrijsku upotrebu. / Suitable for commercial and industrial applications.
 b) Ventilaciono kolo izradjeno od čelika; Napajanje: monofazni 230V-50Hz, trofazni 380V-50Hz.
 Impellers made of steel; Input voltage: single phase 230V-50Hz, three phase 380V-50Hz.
 c) Izolacija klase F, zaštita motora IP54, za temperaturu od -30 do +60 C. / Insulation class F, IP54, for ambient temperature from -30 to +60 C.
 d) Isporučuje sa se priključnom kutijom. / Terminal box included in price.
 e) Regulisanje ventilatora može da se vrši reostatom REM 2,5 ili dvobrzinskim prekidačem DP-2 do z aključno sa modelom 450. Modele 500 i 550 može da reguliše reostat REM 5, a za model 630 koristiti REM 10. Ostali modeli su trofazni i neophodan je frekventni regulator. / Regulation of fans can be done with rheostat REM 2,5 or with two-speed controller DP-2 ending with model 450. Models 500 and 550 can be regulated with rheostat REM 5, and for model 630 should use rheostat REM 10. For bigger models should use frequency inverter.
 f) Regulisanje trofaznih modela se vrši frekventnim regulatorom. / Three speed models can be regulated by frequency controller.
 g) Svi modeli se mogu montirati u vertikalnom ili horizontalnom položaju. / All fan models can be install on the ceiling and one the wall vertically.
 h) Modeli su dostupni u dve boje: JAKKA zelena i crna. / Models are available in two colours: JAKKA green and black.

Označavanje aksijalnih ventilatora / Signaturing for axial fans:

primer / example: JAV4MDI-5-450

JAV : JAK-KA aksijalni ventilator / JAK-KA Axial Fan

Broj polova / Number of poles: 4 (4 - četvorpolni, 6 - šestopolni / 4 poles, 6 poles)

Napajanje / Supply : M (M - monofazni / single phase, T- trofazni / three phase)

Broj brzina / Speed: D (D - dvobrzinski / two speed, T- trobrzinski / three speed)

Smer duvanja / Flow direction: I (I - izvlačenje vazduha / air blowing, U - uvlačenje vazduha / air sucking)

Broj lopatica / Number of blades : 5 (5 ili/or 7)

Prečnik elise / Diameter of propeller : 450

Sve cene su date bez uračunatog PDV / All Prices Are Given Without V.A.T.

