



Model	Napon / Voltage (V)	Snaga / Power (W)	Struja / Current (A)	Kondenzator / Capacitor (μ f)	Brzina / Speed (o/min / rpm)	Protok / Air Flow (m ³ /h)	Jačina zvuka / Sound Level (dB(A))	Dozvoljena spoljna temp. / Permitted Amb. Temp. (°C)	Težina / Weight (kg)	Cena / Price (€)
JILK 100 N	230	80	0,30	2	2.610	240	50	60	2,6	52,00
JILK 125 N	230	80	0,36	2,5	2.325	315	55	60	2,7	54,00
JILK 150B N	230	85	0,38	2,5	2.425	420	55	60	3,2	62,00
JILK 160 N	230	90	0,40	2,5	2.385	390	55	60	3	62,00
JILK 200A N	230	95	0,43	2,5	2.280	735	55	60	4,4	80,00
JILK 200B N	230	122	0,55	4	2.550	870	56	60	4,8	86,00
JILK 250A N	230	124	0,56	4	2.500	1.010	57	60	4,9	na upit on request
JILK 250B N	230	145	0,63	6	2.635	1.150	58	60	5,3	101,00
JILK 315A N	230	190	0,90	6	2.560	1.450	65	50	6,8	117,00
JILK 315B N	230	210	1,10	7	2.660	1.750	65	50	6,9	123,00
JILK 355 N	230	123	0,63	4	1.420	1.300	66	50	9	na upit on request

- a) Višenamenski monofazni ventilator, za prenos vazduha kroz kružne kanale. Moguć rad u bilo kom položaju.
Multipurpose single-phase fan, for the transfer of air through circular ducts. Operation possible in any position.
- b) Zaštita motora IP 44. / IP 44 fan protection.
- c) Dostupni su modeli u zelenoj (green series) i sivoj (grey series) boji. Važi samo za staru seriju i dok traju zalihe.
Models available in green (green series) and grey colours (grey series). Only for old series and until end of stock.
- d) Regulisanje brzine reostatom REM 2,5. / Speed control with REM 2,5 controller.

Sve cene su date bez uračunatog PDV / All Prices Are Given Without V.A.T.

