

## Serija TCB(B/T)x2



Cilindrični aksijalni ventilatori, **tretirani protiv korozije "kataforesis"** osnovom i završnom poliester bojom, opremljen sa 2 motora u kontrarotaciji i 2 aluminijumska ventilaciona kola koja su komplementna, monofazni (TCBBx2) ili trofazni motor (TCBTx2), **IP65**, klasa F <sup>(1)</sup>, sa **termičkom zaštitom**, i priključnom kutijom.

<sup>(1)</sup> Radna temperatura od -40°C do 70°C.

### Motori

Regulacija putem promene napona (modeli 400 i 450). Regulacija putem promene frekvencije (trofazni modeli).

### Napajanje

Monofazno 230V-50Hz

Trofazno 400V-50Hz

## PRIMENA



Magacini



Radionice



Komerrijalni prostori



Pomorska industrija

Kod	Model	Broj	Ø Prečnik	Snaga motora	Max. jačina struje	Nivo šuma	Max. protok	Težina	Cena
		(o/min)	(mm)	(W)	(A)	(dB(A))	(m³/h)	(kg)	<b>2G</b>
5605380400	TCBTx2/4-450	1400	450	1,25	3,40	74	6900	42	<b>1242,00</b>
5605381200	TCBTx2/4-500	1340	500	1,75	3,60	76	9400	50	<b>1377,00</b>
5605382000	TCBTx2/4-560	1360	560	3,12	5,80	78	14300	66	<b>1623,00</b>
5605383800	TCBTx2/4-630	1370	630	4,20	8,00	79	18200	80	<b>1715,00</b>
5605384600	TCBBx2/4-450	1370	450	1,24	5,40	74	6900	42	<b>1259,00</b>
5605385300	TCBBx2/4-500	1300	500	1,70	7,30	76	9400	50	<b>1444,00</b>
5605386100	TCBBx2/4-560	1340	560	3,25	15,50	78	14300	66	<b>1692,00</b>
5605387900	TCBBx2/4-630	1280	630	3,90	19,00	79	18200	80	<b>1729,00</b>

\*Nivo prosečnog pritiska aspiracije

