


## Serija COMPACT TCF(B/T)



Cilindrični aksijalni ventilator sa kućištem koje je tretirano protiv korozije "kataforesis" osnovom i poliester bojom, plastično ventilaciono kolo sa staklenim vlaknima, dinamički balansirano, monofazni (TCFB) ili trofazni motor (TCFT), IP65, klasa F (1), sa ugrađenom termičkom zaštitom, priključna kutija kod monofaznih modela sadrži kondenzator.

(1) Radna temperatura: od -40° do +70°C, osim za modele /2-315/H, /2-355/H, /4-710 i 800 (do +40°C)

### Motori:

Dostupni su modeli sa 2,4,6, i 8 polova, u zavisnosti od verzije. Mogućnost regulacije, osim za dvopolne modele i /4-560/H, /4-630/H.

### Napajanje:

Monofazno 230V-50Hz  
Trofazno 230/400V-50Hz ili 400V-50Hz.

**IP65**

**ATEST**

### PRIMENA



Magacini



Rađonice



Komerčajni prostori



Industrijske sušare



Parkinzi

### Dodatne informacije:

Kretanje vazduha vent. kolo-motor (protok B). Motor-ventilaciono kolo (protok A), na zahtev. Kod trofaznih modela regulacija se vrši inverterom (Verzije E-22), po zahtevu.

Kod	Model	Broj (o/min)	Ø Prečnik (mm)	Snaga motora (W)	Max. jačina struje (A)		Nivo šuma (dB(A))	Max. protok (m³/h)	Težina (kg)	Regulacija brzine	Cena <b>2G</b>
					230 V	400 V					
<b>TROFAZNI</b>											
5603966200	TCFT/2-250/H	2500	250	250	0,9	0,5	65	2160	8,0	-	<b>267,00</b>
5603964700	TCFT/4-250/H	1330	250	60	0,3	0,2	52	1220	8,0	RMT-1,5	<b>247,00</b>
5602463100	TCGT/2-315/G	2600	315	400	1,4	0,8	70	3250	11,0	-	<b>382,00</b>
5602346800	TCFT/4-315/H	1300	315	150	0,6	0,3	54	2350	11,0	RMT-1,5	<b>256,00</b>
5602465600	TCGT/2-355/I	2380	355	520	1,6	0,9	71	4000	13,2	-	<b>319,00</b>
5602326000	TCFT/4-355/H	1260	355	200	0,8	0,5	58	3490	13,2	RMT-1,5	<b>297,00</b>
5602614900	TCFT/6-355/H	875	355	90	0,5	0,3	50	2210	8,0	RMT-1,5	<b>356,00</b>
5602329400	TCFT/4-400/H	1350	400	300	1,4	0,8	60	5070	15,5	RMT-1,5	<b>312,00</b>
5602308800	TCFT/6-400/H	830	400	110	0,5	0,3	52	3400	9,0	RMT-1,5	<b>332,00</b>
5602601600	TCFT/4-450/H	1230	450	500	1,7	1,0	65	6760	21,0	RMT-1,5	<b>385,00</b>
5602086000	TCFT/6-450/H	835	450	190	0,8	0,5	53	4550	20,7	RMT-1,5	<b>388,00</b>
5602842600	TCFT/8-450/H	660	450	130	0,7	0,4	51	3500	13,0	RMT-1,5	
5602327800	TCFT/4-500/H	1350	500	660	2,7	1,6	68	9200	25,0	RMT-2,5	<b>406,00</b>
5602087800	TCFT/6-500/H	840	500	250	0,9	0,5	56	5820	24,8	RMT-1,5	<b>406,00</b>
5602876400	TCFT/8-500/H	625	500	150	0,7	0,4	53	4660	16,0	RMT-1,5	
5602089400	TCFT/4-560/H	1320	560	1210	3,9	2,3	71	12480	34,7	-	<b>583,00</b>
5602846700	TCFT/6-560/H	900	560	410	1,6	0,9	59	8260	33,5	RMT-1,5	<b>432,00</b>
5603387100	TCFT/8-560/H	610	560	230	1,0	0,6	55	5990	22,0	RMT-1,5	
5602044900	TCFT/4-630/H	1420	630	1550	5,2	3,0	72	17060	40,0	-	<b>657,00</b>
5602611500	TCFT/6-630/H	810	630	460	2,0	1,2	60	11000	38,5	RMT-1,5	<b>487,00</b>
5604347400	TCFT/8-630/H	635	630	310	1,3	0,8	57	8340	25,0	RMT-1,5	
<b>MONOFAZNI</b>											
5603904300	TCFB/2-250/H	2500	250	250	1,2	-	65	2160	8,0	-	<b>276,00</b>
5603901900	TCFB/4-250/H	1330	250	60	0,3	-	52	1215	8,0	REB-1	<b>256,00</b>
5602462300	TCGB/2-315/L	2500	315	380	1,7	-	70	3260	11,0	-	<b>442,00</b>
5602330200	TCFB/4-315/H	1300	315	100	0,6	-	54	2350	11,0	REB-1	<b>264,00</b>
5602464900	TCGB/2-355/J	2000	355	460	2,1	-	71	4000	13,2	-	<b>449,00</b>
5602331000	TCFB/4-355/H	1225	355	200	1,0	-	58	3490	13,2	REB-2,5	<b>310,00</b>
5603240200	TCFB/6-355/H	800	355	90	0,5	-	50	2210	8,0	REB-1	<b>344,00</b>
5602347600	TCFB/4-400/H	1200	400	340	1,6	-	60	5070	15,5	REB-2,5	<b>327,00</b>
5602373200	TCFB/6-400/H	750	400	110	0,6	-	52	3400	9,0	REB-1	<b>346,00</b>
5602409400	TCFB/4-450/H	1290	450	480	2,3	-	65	6760	21,0	REB-2,5	<b>401,00</b>
5602610700	TCFB/6-450/H	835	450	220	1,2	-	53	4550	20,7	REB-2,5	<b>403,00</b>
5603846600	TCFB/8-450/H	625	450	130	0,7	-	48	3500	13,0	REB-1	
5602328600	TCFB/4-500/H	1290	500	650	3,0	-	68	9200	25,0	REB-5	<b>427,00</b>
5602088600	TCFB/6-500/H	840	500	290	1,6	-	56	5820	24,8	REB-2,5	<b>411,00</b>
5603374900	TCFB/8-500/H	605	500	160	0,9	-	49	4660	16,0	REB-1	<b>399,00</b>
5602043100	TCFB/4-560/H	1250	560	980	4,9	-	71	12480	34,7	-	<b>597,00</b>
5602084500	TCFB/6-560/H	900	560	420	2,4	-	59	7880	33,5	REB-2,5	<b>457,00</b>
5604105600	TCFB/8-560/H	610	560	240	1,3	-	51	5990	22,0	REB-2,5	
5602090200	TCFB/4-630/H	1200	630	1700	7,6	-	72	17060	40,0	-	<b>689,00</b>
5602432600	TCFB/6-630/H	800	630	510	2,6	-	60	10750	38,5	REB-5	<b>494,00</b>
5603991000	TCFB/8-630/H	585	630	320	1,7	-	52	8340	25,0	REB-2,5	

\* Regulacija kod trofaznih modela (RMT) ili korišćenje frekvencijskog konvertora (VFKB / VFTM) se preporučuje na 400V.

Pogledati opremu za montažu serije TCB(B/T)